



## Product information

### NF-Wire-Plus

#### Wire frame chair.



**Frame** made from curved, welded and chrome-plated steel tubing (d= 12 mm) with a cross brace as a footrest.

**Chairs** in 2 fixed heights for temporary sitting up at sit-stand or stand-up tables.

**Seat and backrest shell** manufactured using a monosandwich process. Made from polypropylene with a hard core and glass-fibre content. With a flexible outside and edge area to prevent uncomfortable pressure points when sitting. Optionally with a tightly upholstered seat and backrest area.

**Equipment and options.** Glide elements for hard and soft floors.

**The following material groups are available:** Frame made of steel tube: M(chrome-plated); Seat and backrest: C7; Fabric cover: S46,51,64,74,78,79,82.

|              |                                               |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |                                                                                       |
|--------------|-----------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|              | Upholstery:<br>Seat 20 mm.<br>Backrest 10 mm. |  |  |  |  |  |  |
| NF-Wire Plus |                                               | <b>32370</b>                                                                        | <b>32371</b>                                                                        | <b>32372</b>                                                                        | <b>32375</b>                                                                          | <b>32376</b>                                                                          | <b>32377</b>                                                                          |
|              | Seat w×h×d mm                                 | 434×650×440                                                                         | 434×670×440                                                                         | 434×670×430                                                                         | 434×830×440                                                                           | 434×850×440                                                                           | 434×850×430                                                                           |
|              | Total w×h×d mm                                | 553×1011×540                                                                        |                                                                                     |                                                                                     | 566×1191×540                                                                          |                                                                                       |                                                                                       |
|              | Distance of seat to floor mm                  | 650                                                                                 | 670                                                                                 |                                                                                     | 830                                                                                   | 850                                                                                   |                                                                                       |
|              | Distance of seat to foot position h mm        | 460                                                                                 | 480                                                                                 |                                                                                     | 460                                                                                   | 480                                                                                   |                                                                                       |
|              | Optimum table height mm                       | 880-950                                                                             |                                                                                     |                                                                                     | 1060-1130                                                                             |                                                                                       |                                                                                       |
|              | Seat shell                                    | L                                                                                   |                                                                                     |                                                                                     |                                                                                       |                                                                                       |                                                                                       |